



UNIVERSAL ACRYLIC, WATER BASED LINER, WITH EXCELLENT PENETRATING PROPERTIES, PROVIDING PERFECT ADHISION AND INSULATION.



DESCRIPTION

Universal acrylic, water based liner, with excellent penetrating properties, providing perfect adhision and insulation.

PRODUCT PROPERTIES

- Dilution 1:1
- Colour blue
- Spread rate 250m²
- Very strong adhesion and rapid drying
- Glossy surface for all kinds of water based paints as well as uniform in the final coating
- Easy application, high penetration and spread rate.

RECOMMENDATIONS FOR USE

It is used in all interior, new, old and painted walls and ceilings, previously painted, for painting of any kind of indoor space, bedrooms, toilets, living rooms, office spaces, services etc. In addition, it is recommended to be applied on external facades.

TECHNICAL DATA

Product identity	
Resin	PVA VEOVA Polymer
Density EN ISO 2811-1	1,15±0,02 gr/ml
Dry residue EN ISO 3251	40%
Dilution degree	50-100%
Viscosity	35 ± 5 KU
Drying time between two coatings	2 - 4 hours
VOC in the ready product (European Directive 2004/42/EC) (g/l)	≤10
VOC ambient emissions Simulation chamber ISO 16000 (mg/m ³)	≤0.2



+1 55 12 258 428
info@dc-industries.us
www.dc-industries.us