



REVITAL COLOR IS A SPECIALLY DESIGNED ADDITIVE FOR USE WITH TILE GROUTS TO IMPROVE THE CHEMICAL AND MECHANICAL RESISTANCE.



### PRODUCT DESCRIPTION

Revital Color is a specially designed additive for use with tile grouts to improve the chemical and mechanical resistance. Revital Color is used in place of water to provide a dense, colorfast grout joint that inhibits stain causing bacteria, mold and mildew growth. Ideal for all interior and exterior grout applications.

### FIELD OF APPLICATION

- For interior and exterior installation
- For walls and floors, wet and dry applications
- For use with Portland cement to make slurry bond coats for mortar beds
- Suitable for use in swimming pools and facades

### LIMITATIONS

- It must keep it in a protected place above +5°C.
- Only use Revital Color at ambient and substrate temperatures between +5°C and +35°C.
- Do not dilute Revital Color when using a smoothing mortar over steel or existing glazed tiles.
- Grouts reinforced with Revital Color are not replacements for waterproofing products.

### APPLICATION PROCEDURE

#### *A) Preparing the substrate*

All surfaces must be mechanically hard, clean, and free of all dirt, paint, grease, concrete sealers, or remaining products. Cementitious screed, plasters, and renders must be cured (28 days for cement screeds, 7 days per cm of thickness for plasters). Expansion joints shall be provided through the finishes from all construction or expansion joints in the substrate. Screeds and cement mortar beds that are particularly absorbent or subject to overheated by the sun must be saturated without leaving water on the surface.

#### *B) Preparing the product*

The mixing water of tile grouts is replaced with Revital Color until a final homogenized product is achieved. Then, the product is applied according to the description given on the product data sheet.

## COVERAGE / CONSUMPTION

Depending on the application. The suggested dosage is from 1Kg up to 5kg per bag of cement base products depending on the performance to be achieved.

## PACKAGING

Revital Color is supplied in:

- 1 kg plastic can
- 5 kg plastic can
- 10 kg plastic can

## SHELF LIFE-STORAGE

Original sealed packaging of this product is guaranteed to be of first quality for 24 months if stored in a dry area. In places with high humidity will reduce the shelf life of the bagged product.

## SAFETY INSTRUCTION

REVITAL COLOR is not considered dangerous according to the current regulations regarding the classification of mixtures. However, it is recommended to wear protective gloves and goggles and take the usual precautions for handling chemicals. For further information about the safe use of our product, please refer to the latest version of our Material Safety Data Sheet. PRODUCT FOR PROFESSIONAL USE.

## TECHNICAL DATA

Product identity	
Consistency	Liquid
Color	White
Density (kg/m <sup>3</sup> )	100
Viscosity (mPa.s)	350
Dry solids content (%)	25
pH of mix	8
Application temperature	+5°C to +35°C



+1 55 12 258 428  
info@dc-industries.us  
www.dc-industries.us