

## DC BASICS



### DESCRIPTION

Concentrated pigments used for the pigmentation of PVA-VEOVA based paints

### PRODUCT PROPERTIES

- Easily spread
- Strong painting capacity
- For indoor use

### RECOMMENDATIONS FOR USE

It is used for the pigmentation of water based paints, of the plastic lines and hydro mats only for W basis. It can be mixed with an electric mixer.

### PRODUCT PREPARATION

First, mix the product in its original package, than it is used in its condition or is dosed in paint for its colouring.

### PACKAGING

0.180 lt, 0.375 lt, 0.750 lt

### STORAGE

36 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C. Protect it from frost.

### HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advise immediately and show the contents of the container. Do not dispose the product into drains.

### TECHNICAL DATA

Basis	Water pigment dispersion
Form	Liquid
Colour	Grey, Green, Yellow, Okra, Orange, etc...
Density EN ISO 2811-1	1,55±0,02 gr/ml
Dilution ratio	Ready for use
Viscosity	25 ± 5 KU
Reaction time	10 – 20 minutes
VOC in the ready product (European Directive 2004/42/EC) (g/l)	≤ 50
VOC ambient emissions Simulation chamber ISO 16000 (mg/m3)	≤ 10

