

PICASSO CLASSIC VN-35 ULTRA WHITE



DESCRIPTION

Premium quality plastic paint produced with the most advanced "One Coat" technology with high resistance to continuous washing and superior covering properties with emulsion-based PVA-VEOVA

PRODUCT PROPERTIES

- Whiteness and twinkling
- Superior covering
- Finished surface matt
- Available only in the base W
- Very strong adhesion and rapid drying
- High resistance to frequent washings
- Excellent workability and levelling
- Supports 7000 washing cycles 30 days after the application

RECOMMENDATIONS FOR USE

It is used in all interior, new, old and painted walls and ceilings, previously painted with cement base paint, lime, gypsum, and any kind of indoor space, bedrooms, toilets, living rooms, office spaces, services etc.

TECHNICAL DATA

Resin	Acrylic copolymer
Density EN ISO 2811-1	1,35±0,02 gr/ml
Dry residue EN ISO 3251	50%
Dilution degree	10 – 30%
Viscosity	115 ± 5 KU
Drying time between two coatings	2 - 4 hours
VOC in the ready product (European Directive 2004/42/EC) (g/l)	≤ 10
VOC ambient emissions Simulation chamber ISO 16000 (mg/m3)	≤ 0.2

APPLICATION GUIDELINES

- Application method: Brush, roller or spraying.
- Thinning: It is recommended to be diluted 10-15% with water.

SURFACE PREPARATION

The surfaces should be completely dry, clean and free from dust and elements that hinder the adhesion of the paint. Repair all cracks and damaged parts using the line products of Deutschcolor, Vox 707, Glatte Spachtel, Spachtel Finish etc. Then, it is recommended to apply the Macht Tiefgrund Wasser liner, diluted with 1:1 water or a water-diluted Macht Haftgrund liner at 1:3 ratio. When applying the liner, avoid creating a film, which then creates problems in gluing the paint to the support.

PRODUCT PREPARATION

Dilute the product Picasso Classic VN-35 Ultra White with 10-15% water, making sure it is fully mixed with the paint. Use a low speed electric mixer to make a mixture as uniform and complete as possible.

APPLICATION OF PRODUCT

Product Application Picasso Classic VN-35 Ultra White is applied by brush or roller. At least one paint coat must have been applied. Drying time for the first layer is 2-4 hours depending on weather conditions, temperature and humidity. Clean brushes, rollers and other working tools with water before the paint dries.

PACKAGING

3 lt, 10 lt

STORAGE

36 months if stored in a dry place, away from heat sources, at a temperature between +5°C and +30°C. Protect it from frost.

HEALTH AND SAFETY INFORMATION

Keep out of reach of children. In case of contact with the eyes or swallowing, please seek medical advice immediately and show the contents of the container. Do not dispose the product into drains.

NOTES

- It is recommended not to wash the painted surfaces until 30 days after application.
- In fresh concrete surfaces the product should be applied at least after 30-40 days.

